

## Downlight Panel Armatürler

## Downlight Panel Luminaires



Genel aydınlatma armatürü olarak kullanılan Compact ürünümüz downlight armatür sınıfında kullanılan PLC klasik armatürlerinin yerine kullanılmaktadır. İlk armatür içinde kalması ile şık görünümlü ve ışık verimliliği klasik armatürlere nazaran daha iyi olan bu armatürümüz, mimari yapılarda, genel aydınlatma projelerinde rahatlıkla kullanılmaktadır. Genel kullanım alanları ofisler, konutlar, hoteller, kamu alanları vb. yerlerdir.

Oxiron Compact luminaire used for general lighting is used in place of conventional PLC Downlight luminaire. Oxiron Compact, in terms of lighting efficiency compared to conventional luminaires is superior and can be used easily in architecture general lighting projects. General application fields are offices, hotels, public spaces etc.






## Square

OX 126 01 103

## Genel Özellikler Key Features

Gövde Tipi Body Type	Elektrostatik Toz Boya Kaplamalı Alüminyum Electrostatic Power Coated Aluminum
Gövde Boya Rengi Body Colour	Standart Mat Beyaz (RAL 9010) Standart Matte White (RAL 9010)
İşik Rengi Luminous Colour - Kelvin	3000K-4000K-6500K 3000K-4000K-6500K
IP Sınıfı IP Degree	IP44 IP44
Renksel Geri Verimlilik Colour Rendering Index - CRI	>80 >80
Difüzör Diffuser	UV Filtreli Opal veya 3D Difüzörlü UV Filtered Diffuser or 3D Diffuser
LED Ömrü Life Time	50.000 Saat 50.000 Hours
Güç Faktörü Power Factor	>0,90 >0,90
Giriş Gerilimi Input Voltage	220-240V AC 50Hz 220-240V AC 50Hz
Sürücü Driver	Philips, Osram, Meanwell, Tridonic veya Eagle Rise Philips, Osram, Meanwell, Tridonic or Eagle Rise
Kontrol Tipi Control Type	ON/OFF, Dali, 1-10V, 0-10V veya KNX ON/OFF, Dali, 1-10V, 0-10V or KNX
Eklenebilir Özellikler Additional Options	1/2/3 Saatlik Acil Aydınlatma Kiti, Hareket Sensörü, Gövde Rengi (RAL XXXX), 1/2/3 Hours Emergency Kit, Motion Sensor, Body Colour (RAL XXXX)
Uygulama Opsiyonları Application Options	Sıva Altı Recessed Mounted



Ürün Kodu Product Code	Tip Type	Güç Power	İşik Akısı Lighting Fux	En Width	Boy Length	Yükseklik Height	Tavan Kesim Çapı Ceiling Cut Diameter
		W	lm	A (mm)	B (mm)	H (mm)	R' (mm)
OX126 01103 006	2"	6	600	97	97	55	85
OX126 01103 008	3"	8	800	117	117	50	105
OX126 01103 012	4"	12	1200	147	147	55	130
OX126 01103 016	5"	16	1600	175	175	58	160
OX126 01103 020	6"	20	2000	192	192	55	175
OX126 01103 026	8"	26	2600	227	227	58	210

